




Single Output 30 to 60W Medical & ITE Power Supplies

Features	Benefits
• High Efficiency, up to 90%	• Easier Thermal Management
• Compact 2" x 3" Footprint	• Space Saving
• Convection Cooled	• Quiet Operation
• Suitable for Class I and II Installations	• Flexible Utilisation
• Medical Approval with 2 x MoPP Isolation	• Suitable for B and BF Rated Equipment



Specification		
Model	CUS30M	CUS60M
AC Input Voltage	VAC	85 - 265VAC ⁽¹⁾
Input Frequency	Hz	47 - 63Hz
Inrush Current (cold start)	A	30A at 115VAC, 60A at 230VAC
Power Factor	-	Meets EN61000-3-2
Input Current (115/230VAC)	A	0.6 / 0.4 5V: 0.7 / 0.5, 12-48V: 1.2 / 0.8
Off-load Power Draw	W	<0.3W at 265VAC <0.5W at 265VAC
Temperature Coefficient	%/°C	<0.02%/°C
Overcurrent Protection	-	>105% of rated current, Class 2 Limited Power Source ⁽²⁾
Overvoltage Protection ⁽³⁾	V	> 115% of nominal output > 120% of nominal output
Hold Up Time (Typical) (115/230VAC)	ms	20 / 100
Leakage Current	mA	<0.25mA at 265VAC, 60Hz <0.2mA at 265VAC, 60Hz
Touch Current (Maximum)	µA	100µA at 265VAC, 60Hz 60µA at 265VAC, 60Hz
Remote Sense	-	No
Operating Temperature	°C	-20°C to +70°C. (-30°C start up) Derate linearly to 50% load from +50°C to +70°C ⁽⁴⁾
Storage Temperature	°C	-40°C to +85°C
Humidity (non condensing)	%RH	10 - 95%RH (Operating & Storage)
Cooling	-	Convection Cooled
Withstand Voltage	-	Input to Ground 2kVAC (1xMOPP), Input to Output 4kVAC (2xMOPPs), Output to Ground 1.5kVAC (1xMOPP) suitable for B & BF rated equipment
Isolation Resistance	MΩ	>100MΩ at 25°C & 70%RH, Output to Ground 500VDC
Vibration (non operating)	-	10 - 55Hz: 19.6m/s ² constant sweep 1 min X, Y, Z for 1 hour
Shock	-	< 196.1 m/s ² , MIL-STD-810F
Immunity	-	IEC61000-4-2 (lv 4), -3 (lv 3), -4 (lv 3), -5 (lv 3, 4), -6 (lv 3), -8 (lv 4), -11, Criteria A. IEC60601-1-2 Ed4 SEMIF47 (200-240VAC), IEC61000-4-11 (Class 3)
Line Voltage Dips	-	Criteria A: Vin >120VAC, or <70% load, Criteria B: Vin <120VAC, and >70% load
Safety Agency Certifications	-	EN/IEC/UL/ES/CSA60601-1, EN/IEC/UL/CSA60950-1, CE Mark, IEC60335-1
Altitude	m	5,000m, derate operating ambient by 5°C/1000m above 3,000m
Conducted & Radiated EMI	-	EN55011-B, EN55032-B, FCC Class B
Weight (Typ)	g	62 120
Size (LxWxH)	mm	76.2 x 50.8 x 24.2 76.2 x 50.8 x 26.7
Warranty	yrs	3

Notes:

(1) CUS30M: Derate linearly to 80% load from 115VAC to 85VAC. CUS60M: Derate linearly to 80% load from 100VAC to 85VAC

(2) All models except CUS60M-5

(3) Cycle AC to reset

(4) CUS30M-18 and -48, CUS60M-5 and -12: Derate linearly to 50% load from +45 to +70°C

Model Selector


Model	Voltage	Max Current (A)	Max Power (W)	Load Reg (mV)	Line Reg (mV)	Ripple Noise (mV) ⁽⁵⁾	Efficiency (typ) % ⁽⁶⁾	Average Active Efficiency (typ) % ⁽⁶⁾
CUS60M-5*	5V	6.0	30.0	100	20	120	81 / 81	81 / 80
CUS30M-12	12V	2.5	30.0	120	48	120	87 / 88	87 / 87
CUS60M-12	12V	5.0	60.0	120	48	120	87 / 88	87 / 86
CUS30M-15 [†]	15V	2.0	30	120	60	150	87 / 88	87 / 87
CUS60M-15*	15V	4.0	60	120	60	150	88 / 89	87 / 87
CUS30M-18 [†]	18V	1.7	30.6	144	72	150	87 / 88	87 / 87
CUS60M-18*	18V	3.25	60.3	144	72	150	88 / 89	87 / 87
CUS30M-24	24V	1.25	30.0	192	96	150	88 / 90	87 / 87
CUS60M-24	24V	2.5	60.0	192	96	150	89 / 90	88 / 87
CUS30M-36 [†]	36V	0.84	30.24	288	144	200	88 / 90	87 / 87
CUS60M-36 [†]	36V	1.68	60.48	288	144	200	89 / 90	88 / 87
CUS30M-48	48V	0.63	30.24	384	192	200	88 / 90	87 / 87
CUS60M-48*	48V	1.25	60.0	384	192	200	89 / 90	89 / 88

Notes:


(5) Ripple level increases at light loading to meet new efficiency standards (6) 115/230VAC

* Available Q2 2018 [†] Contact Sales for Availability

Outline Drawing CUS30M Series



Outline Drawing CUS60M Series



Options (available on request)

Suffix	Description
Blank	Open Frame Construction, Fixed Output
/ ADJ	Output Voltage Adjustment Potentiometer ($\pm 10\%$ Range)



TDK-Lambda France SAS

3 Avenue du Canada
Parc Technopolis
Bâtiment Sigma
91940 les Ulis
France
Tel: +33 1 60 12 71 65
Fax: +33 1 60 12 71 66
france@fr.tdk-lambda.com
www.fr.tdk-lambda.com



Italy Sales Office

Via dei Lavoratori 128/130
20092 Cinisello Balsamo (MI)
Italy
Tel: +39 02 61 29 38 63
Fax: +39 02 61 29 09 00
info.italia@it.tdk-lambda.com
www.it.tdk-lambda.com



Netherlands

info@nl.tdk-lambda.com
www.nl.tdk-lambda.com



TDK-Lambda Germany GmbH

Karl-Bold-Strasse 40
77855 Achern
Germany
Tel: +49 7841 666 0
Fax: +49 7841 5000
info.germany@de.tdk-lambda.com
www.de.tdk-lambda.com



Austria Sales Office

Aredstrasse 22
2544 Leobersdorf
Austria
Tel: +43 2256 655 84
Fax: +43 2256 645 12
info@at.tdk-lambda.com
www.de.tdk-lambda.com



Switzerland Sales Office

Bahnhofstrasse 50
8305 Dietlikon
Switzerland
Tel: +41 44 850 53 53
Fax: +41 44 850 53 50
info@ch.tdk-lambda.com
www.de.tdk-lambda.com



Nordic Sales Office

Haderslevvej 36B
DK-6000 Kolding
Denmark
Tel: +45 2911 9556
info@dk.tdk-lambda.com



TDK-Lambda UK Ltd.

Kingsley Avenue
Ilfracombe
Devon EX34 8ES
United Kingdom
Tel: +44 (0) 12 71 85 66 66
Fax: +44 (0) 12 71 86 48 94
powersolutions@uk.tdk-lambda.com
www.uk.tdk-lambda.com



TDK-Lambda Ltd.

Kibbutz
Givat Hashlosa 48800
Israel
Tel: +9 723 902 4333
Fax: +9 723 902 4777
info@tdk-lambda.co.il
www.tdk-lambda.co.il



C.I.S.

Commercial Support:

Tel: +7 (495) 665 2627

Technical Support:

Tel: +7 (812) 658 0463
info@tdk-lambda.ru
www.tdk-lambda.ru

Local Distribution

