

AC AXIAL FAN 172x150x51mm



Housing: Die-Cast Aluminum, Painted Black
 Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 100M Ω , 500VDC/min between bare wire and frame
 Dielectric Strength: 1500VAC for one minutue
 Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
 Storage Temperature: -40°C~85°C(Humidity 35%-85%RH)
 Motor Protection: Impedance Protected
 Weight: 920 g Packing: 16PCS/CTN



SS IP

Model Number	Voltage (VAC)	Frequency (Hz)	Air Flow (CFM)	Stat.Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FA1751B11T5-96	115	50/60	141.1/176.6	10.3/12.4	42.4/47.3	2,350/2,550	400/380	28/27	B,S	①/②
FA1751B11T7-96	115	50/60	198.9/211.1	12.6/13.4	47.3/54.2	2,500/2,700	500/440	39/36	B,S	③/④
FA1751B22T5-96	230	50/60	141.1/176.6	10.3/12.4	42.4/47.3	2,350/2,550	180/170	25/24	B,S	①/②
FA1751B22T7-96	230	50/60	198.9/211.1	12.6/13.4	47.3/54.2	2,500/2,700	240/220	37/35	B,S	③/④

- For "Sleeve" bearing version, change the "B" in the model number to "S".
- For "Wire Lead" version, change the "T" in the model number to "W".

Specifications are subject to change without notice

