

# DC BLOWER 93x93x30mm



**Housing/Blade:** Thermoplastic PBT, UL 94V-0  
**Insulation Resistance:** 10MΩ, 500VDC/min between bare wire and frame  
**Dielectric Strength:** 5mA max. 500VAC/min between bare wire and frame  
**Operation Temperature:** -10°C~70°C(Humidity 35%-85%RH)  
**Storage Temperature:** -40°C~70°C(Humidity 35%-85%RH)  
**Lead Wire:** UL Type #24 AWG  
**Weight:** 155 g      **Packing:** 60PCS/CTN



SS

IP

SF

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FBD9330B12W1-61	▲ 12	6.0~13.8	13.20	6.40	37.40	2,100	180	2.16	B,S	①
FBD9330B12W3-61	★▲ 12	6.0~13.8	16.00	10.20	41.40	2,500	290	3.48	B,S	②
FBD9330B12W5-61	★★▲ 12	6.0~13.8	19.50	19.10	44.30	3,000	490	5.88	B,S	③
FBD9330B24W1-61	▲ 24	12.0~27.6	13.20	6.40	37.40	2,100	80	1.92	B,S	①
FBD9330B24W3-61	★▲ 24	12.0~27.6	16.00	10.20	41.40	2,500	140	3.36	B,S	②
FBD9330B24W5-61	★★▲ 24	12.0~27.6	19.50	19.10	44.30	3,000	230	5.52	B,S	③

- For "Sleeve" bearing version, change the "B" in the model number to, "S".
- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

