

DC AXIAL FAN 20x20x06mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
Storage Temperature: -40°C~70°C(Humidity 35%-85%RH)
Lead Wire: UL Type #28 AWG
Weight: 4 g **Packing:** 400PCS/CTN



SS

SF



DC Axial Fans

Model Number		Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD2006S05W5-71	★	5	4.0~5.5	0.90	2.30	26.40	10,000	90	0.45	S	①
FD2006S05W7-71	★	5	4.0~5.5	1.40	5.30	39.10	15,000	140	0.70	S	②
FD2006S12W5-71	★	12	10.8-13.2	0.90	2.30	26.40	10,000	100	1.20	S	①
FD2006S12W7-71	★	12	10.8-13.2	1.40	5.30	39.10	15,000	110	1.32	S	②

• If model depicts "★", auto restart protection function built in.

Specifications are subject to change without notice

