

DC AXIAL FAN 30x30x10mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
Insulation Resistance: 10M Ω , 500VDC/min between bare wire and frame
Dielectric Strength: 5mA max., 500VAC/min between bare wire and frame
Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
Lead Wire: UL Type #28 AWG
Weight: 8 g **Packing:** 600PCS/CTN



DC Axial Fans

Model Number	Voltage (VDC)	Op. Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD3010B05W3-82	5	4.5~5.5	3.00	2.00	13.80	6,000	110	0.55	B,S	①
FD3010B05W5-82	5	4.5~5.5	4.10	3.80	23.60	8,500	140	0.70	B,S	②
FD3010B05W7-82	5	4.5~5.5	4.90	5.20	28.10	10,000	190	0.95	B,S	③
FD3010B12W3-82	12	10.8~13.8	3.00	2.00	13.80	6,000	60	0.72	B,S	①
FD3010B12W5-82	12	9.0~13.8	4.10	3.80	23.60	8,500	100	1.20	B,S	②
FD3010B12W7-82	12	9.0~13.8	4.90	5.20	28.10	10,000	140	1.68	B,S	③

• For "Sleeve" bearing versions, change the "B" in the model number to "S".

Specifications are subject to change without notice

