

# DC AXIAL FAN 40x40x10mm



Housing/Blade: Thermoplastic PBT, UL 94V-0  
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame  
 Dielectric Strength: 5mA max, 500VAC/min between bare wire and frame  
 Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)  
 Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)  
 Lead Wire: UL Type #28 AWG  
 Weight: 11 g      Packing: 400PCS/CTN



DC Axial Fans

Model Number	Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD4010B12W3-75	12	7.0~13.8	4.50	2.20	23.10	4,600	70	0.84	B,S	①
FD4010B12W5-75	12	7.0~13.8	5.40	2.90	27.80	5,500	90	1.08	B,S	②
FD4010B12W7-75	12	7.0~13.8	6.40	4.10	30.50	6,400	100	1.20	B,S	③
FD4010B12W9-75	12	7.0~13.8	7.30	5.10	33.40	7,300	120	1.44	B,S	④
FD4010B12W11-75	12	7.0~13.8	8.30	6.50	36.20	8,200	130	1.56	B,S	⑤
FD4010B24W3-75	24	12.0~27.6	4.50	2.20	23.10	4,600	60	1.44	B,S	①
FD4010B24W5-75	24	12.0~27.6	5.40	2.90	27.80	5,500	70	1.68	B,S	②
FD4010B24W7-75	24	12.0~27.6	6.40	4.10	30.50	6,400	80	1.92	B,S	③
FD4010B24W9-75	24	12.0~27.6	7.30	5.10	33.40	7,300	90	2.16	B,S	④
FD4010B24W11-75	24	12.0~27.6	8.30	6.50	36.20	8,200	100	2.40	B,S	⑤

• For "Sleeve" bearing version, change the "B" in the model number to "S".

Specifications are subject to change without notice

