

# DC AXIAL FAN 60x60x25mm



Housing/Blade: Thermoplastic PBT, UL 94V-0  
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame  
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame  
 Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)  
 Storage Temperature: -40°C~70°C(Humidity 35%-85%RH)  
 Lead Wire: UL Type #26 AWG  
 Weight: 68 g      Packing: 200PCS/CTN



**SS** **IP** **SF**

DC Axial Fans

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD6025B12W3-75	12	7.0~13.8	16.20	2.80	26.40	3,000	150	1.80	B,S	①
FD6025B12W5-75	★ 12	7.0~13.8	25.70	6.50	38.50	4,800	270	3.24	B,S	③
FD6025B12W7-75	★ 12	7.0~13.8	32.80	9.90	45.60	6,000	320	3.84	B,S	⑤
FD6025B12W9-75	★ 12	7.0~13.8	37.50	12.70	48.30	6,800	350	4.20	B,S	⑥
FD6025B24W3-75	24	12.0~27.6	16.20	2.80	26.40	3,000	90	2.16	B,S	①
FD6025B24W5-75	★ 24	12.0~27.6	25.70	6.50	38.50	4,800	170	4.08	B,S	③
FD6025B24W7-75	★ 24	12.0~27.6	32.80	9.90	45.60	6,000	220	5.28	B,S	⑤
FD6025B24W9-75	★ 24	12.0~27.6	37.50	12.70	48.30	6,800	290	6.96	B,S	⑥
FD6025B48W3-75	★ 48	24.0~56.0	22.40	5.10	35.20	4,200	50	2.40	B,S	②
FD6025B48W5-75	★ 48	24.0~56.0	25.70	6.50	38.50	4,800	80	3.84	B,S	③
FD6025B48W7-75	★ 48	24.0~56.0	29.60	8.30	40.30	5,400	120	5.76	B,S	④
FD6025B48W9-75	★ 48	24.0~56.0	32.80	9.90	45.60	6,000	180	8.64	B,S	⑤

- For "Sleeve" bearing version, change the "B" in the model number to "S".
- If model depicts "★", auto restart protection function built in.

Specifications are subject to change without notice

