

DC AXIAL FAN 60x60x25mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
 Storage Temperature: -40°C~70°C(Humidity 35%-85%RH)
 Lead Wire: UL Type #26 AWG
 Weight: 55 g Packing: 200PCS/CTN



DC Axial Fans

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD6025B12W1-71	12	10.8~13.2	13.40	1.20	18.70	2,500	80	0.96	B,L,S	①
FD6025B12W3-71	12	10.8~13.2	16.10	2.40	22.10	3,000	80	0.96	B,L,S	②
FD6025B12W5-71	12	10.8~13.2	21.40	4.80	28.90	4,000	130	1.56	B,L,S	③
FD6025B24W1-71	24	17.0~28.0	13.40	1.20	18.70	2,500	90	2.16	B,L,S	①
FD6025B24W3-71	24	17.0~28.0	16.10	2.40	22.10	3,000	100	2.40	B,L,S	②
FD6025B24W5-71	24	17.0~28.0	21.40	4.80	28.90	4,000	140	3.36	B,L,S	③

• For "Long Life", or "Sleeve" bearing versions, change the "B" in the model number to "L", or "S" respectively.

Specifications are subject to change without notice

