

ZPSA20 Series

2" x 3.5" 20W AC-DC
Power Supplies

- Wide Range AC Input
- Low Profile, Industry Standard Footprint
- Global Safety Agency Compliance
- RoHS Compliant

Key Market Segments & Applications

Video/Audio Routers
Datacom
Point of Sale
Test and Measurement
LED Signs and Lighting

ZPSA20 Features and Benefits

Features

- Industry Standard Footprint
- Up to 82% efficiency
- Broad Product Range
- Meets EN61000-4 Immunity

Benefits

- Available to Second Source
- Less System Heating
- Optimization of Power Supply to System
- Greater Reliability

Specifications

ITEMS		MODEL	ZPSA20
Input Voltage range	(1)	-	85 - 264VAC (47 - 440Hz) or 120 - 370VDC
Inrush Current		A	40A max at 240VAC input, 25°C ambient cold start,
Input Current (115/230VAC)		A	0.4 / 0.25
Leakage Current		mA	0.6mA maximum (264VAC, 60Hz)
Temperature Coefficient		-	±0.05%/°C
Voltage Accuracy		-	±1%
Minimum Load		A	None
Load Regulation		-	±1%
Line Regulation		-	±0.5%
Ripple & Noise	(2)	mV	1% or 50mV whichever is greater
Short Circuit Protection		-	Continuous - hiccup mode
Overvoltage Protection		V	Typically 110-130% of nominal
Hold Up Time (Typ)		ms	12ms at 115VAC input
Operating Temperature			0 to +70°C with derating
Storage Temperature		-	-20 to +85°C
Humidity (non condensing)		-	10 - 95% RH
Cooling		-	Convection
Withstand Voltage			Input to Ground 1.5kVAC, Input to Output 3kVAC, Output to Ground 500VAC for 1 min.
Isolation Resistance			>100ΩM at 25°C & 70%RH, Output to Ground 500VDC
Vibration (non operating)			23.52m/s ² (10 - 55Hz: constant sweep 1 min X, Y, Z for 1 hour)
Shock		-	< 196.1 m/s ² (20G)
Safety Agency Approvals		-	UL60950, CSA60950, EN60950-1 Class 1, CE Mark (LVD)
Conducted & Radiated EMI		-	EN55022-B, FCC Class B
Immunity		-	EN61000-4-2,-3,-4,-6,-8
Weight (Typ)		g	100g
Size (WxLxH)		mm	88.9 X 50.8 X 20.32 (including underside components)
Warranty		yrs	2

Notes:


(1) Safety certified for 47 - 63Hz input only (2) Measured with 0.1μF ceramic & 10μF electrolytic at 20MHz BW

Model Selector

Model	Output Voltage (V)	Maximum Output (A)	Peak Load (A) (1)	Efficiency (2) (typ)%
ZPSA20-3R3 V1	3.3	4.4	6.6	74
ZPSA20-5 V1	5.0	4.4	6.6	77
ZPSA20-9 V1	9.0	2.4	4.0	80
ZPSA20-12 V1	12.0	1.8	2.7	80
ZPSA20-15 V1	15.0	1.4	2.1	80
ZPSA20-24 V1	24	0.9	1.4	82


Notes: (1) Average not to exceed max power, <30s, 10% duty cycle (high line 240VAC)
 (2) Preliminary Data

Derating Curve ZPSA20 Series



**INTERMEDIATE VOLTAGES AVAILABLE
 PLEASE CONSULT SALES**

Outline Drawing ZPSA20 Series



Options
Suffix
Add Suffix -P for PCB Mount Pins



TDK-Lambda France SAS

ZAC des Delaches
 CS 41077
 9 rue Thuillere
 91978 Villebon Courtaboeuf
 France
 Tel: +33 1 60 12 71 65
 Fax: +33 1 60 12 71 66
france@fr.tdk-lambda.com
www.fr.tdk-lambda.com



Italy Sales Office

Via dei Lavoratori 128/130
 20092 Cinisello Balsamo (MI)
 Italy
 Tel: +39 02 61 29 38 63
 Fax: +39 02 61 29 09 00
info.italia@it.tdk-lambda.com
www.it.tdk-lambda.com



Netherlands

info@tdk-lambda.nl
www.tdk-lambda.nl



TDK-Lambda Germany GmbH

Karl-Bold-Strasse 40
 77855 Achern
 Germany
 Tel: +49 7841 666 0
 Fax: +49 7841 5000
info.germany@de.tdk-lambda.com
www.de.tdk-lambda.com



Austria Sales Office

Aredstrasse 22
 2544 Leobersdorf
 Austria
 Tel: +43 2256 655 84
 Fax: +43 2256 645 12
info.germany@de.tdk-lambda.com
www.de.tdk-lambda.com



Scandinavia Sales Office

Valdemarsgade 7
 4100 Ringsted
 Denmark
 Tel: +45 24 63 95 65
 Fax: +45 69 80 44 99
info@de.tdk-lambda.com
www.emea.tdk-lambda.com



Switzerland Sales Office

Bahnhofstrasse 50
 8305 Dietlikon
 Switzerland
 Tel: +41 44 850 53 53
 Fax: +41 44 850 53 50
info@de.tdk-lambda.com
www.de.tdk-lambda.com



TDK-Lambda UK Ltd.

Kingsley Avenue
 Ilfracombe
 Devon EX34 8ES
 United Kingdom
 Tel: +44 (0) 12 71 85 66 66
 Fax: +44 (0) 12 71 86 48 94
powersolutions@uk.tdk-lambda.com
www.uk.tdk-lambda.com



TDK-Lambda Ltd.


Kibbutz
 Givat Hashlosha 48800
 Israel
 Tel: +9 723 902 4333
 Fax: +9 723 902 4777
info@tdk-lambda.co.il
www.tdk-lambda.co.il



C.I.S.

Commercial Support:
 Tel: +7 (495) 665 2627
Technical Support:
 Tel: +7 (812) 658 0463
info@tdk-lambda.ru
www.tdk-lambda.ru

Local Distribution



www.emea.tdk-lambda.com